



## **X1 WHITE GREASE**

# **Excellent lubrication, water and heat resistance.**

- Stops squeaking
- Water repellent
- Corrosion preventive
- Suitable for vertical surfaces, will not run

## KNOW-HOW TO PROTECT™

## WWW.RUST-OLEUM.EU

## **X1 WHITE GREASE**

#### DESCRIPTION

Multi purpose, high quality white grease giving excellent lubrication, water and heat resistance. Reinforced with BoroTecX<sup>™</sup> extends its working life and improves the greases ability to withstand extreme loads and conditions. The White Grease spray is formulated to penetrate linkages, hinges, chains before setting to leave a tenacious long lasting lubricant.

#### **RECOMMENDED USE**

Lubricating bearings, gears, cables and chains etc. Protection of metal surfaces against rust. Lubricating locks, hinges, and other moving parts. Ideal for tracks and slide conveyors. Water resistant, can be used on water pumps etc

### **TECHNICAL DATA**

#### DRYING TIMES AT 20°C/RH 50%

### SURFACE PREPARATION

Ensure electrical equipment is isolated and check surfaces for compatibility prior to application. Clean and remove old lubricant from components prior to application.

#### **APPLICATION CONDITIONS**

Apply at temperatures between 5° and 35°C.

Shake aerosol before use. Spray a light film onto surface from 20 to 30 cm. Do not over apply

#### SAFETY DATA

Remarks regarding safety: Consult Safety Data Sheet and Safety Information printed on the can.

#### SHELF LIFE

3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 12/04/2018

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular ourpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification

#### st-Oleum Netherlands B.V.

Zilverenberg 16 5234 GM 's-Hertogenbosch The Netherlands T : +31 (0) 165 593 636 F: +31 (0) 165 593 600

## Rust-Oleum UK Ltd. PO Box 261 Chester-le-Street

info@rus

DH3 9EH United Kingdom T : +44 (0)1914 113 146 F: +44 (0)1914 113 147

Rust-Oleum France S.A.S. 11, rue Jules Verne - B.P. 60039 95322 St-Leu-La-Forêt Cedex France : +33(0) 130 40 00 44 F: +33(0) 130 40 99 80 info@rust-oleum.eu

N.V. Martin Mathys S.A Kolenbergstraat 23 3545 Zelem Belgium T : +32 (0) 13 460 200 F: +32 (0) 13 460 201



## WWW.RUST-OLEUM.EU